

FLOORS 20 MM

Mystone Pietra Ligure20



MARAZZI



Mystone Pietra Figure20

Between light, matter and landscape, a surface takes shape to give continuity to outdoor spaces. Mystone Pietra Figure20 is available in Bianco, Beige, Cenere and Antracite, in 60x60 and 60x120 sizes. The Tecnico finish ensures reliability and design continuity for residential and commercial settings. The 20 mm version expands installation possibilities and strengthens the dialogue between surface and exterior architecture, with a clear outdoor vocation today.










Mystone Pietra Ligure20 Index


Mystone Pietra Ligure20

- Colorbody Fine Porcelain Stoneware · Porcelain Stoneware




Antracite

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
60x120cm	Structured Surface	MPLA	Mystone Pietra Ligure20 Antracite Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V3	1	0,72	32,06	36	25,92	1.154,05	
60x60cm	Structured Surface	MPLH	Mystone Pietra Ligure20 Antracite Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V3	2	0,72	32,56	32	23,04	1.042,06	




Beige

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
60x120cm	Structured Surface	MPLD	Mystone Pietra Ligure20 Beige Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V3	1	0,72	32,29	36	25,92	1.162,33	
60x60cm	Structured Surface	MPLF	Mystone Pietra Ligure20 Beige Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V3	2	0,72	32,85	32	23,04	1.051,10	



Bianco

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
60x120cm	Structured Surface	MPLC	Mystone Pietra Ligure20 Bianco Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V3	1	0,72	32,35	36	25,92	1.164,42	
60x60cm	Structured Surface	MPLF	Mystone Pietra Ligure20 Bianco Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V3	2	0,72	32,61	32	23,04	1.043,48	



Cenere

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
60x120cm	Structured Surface	MPL9	Mystone Pietra Ligure20 Cenere Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V3	1	0,72	32,24	36	25,92	1.160,77	
60x60cm	Structured Surface	MPLG	Mystone Pietra Ligure20 Cenere Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V3	2	0,72	32,20	32	23,04	1.030,41	

Legenda

Destinazioni d'uso

D
Tiles suitable only for residential bathrooms and bedrooms; any type of abrasion must be avoided.

E
Tiles suitable for any room of a house except for entrance areas and kitchens. Low stress abrasive wear.

F
Tiles suitable for any room of a house without direct access from the outside or access not protected by doormats. Average stress abrasive wear.

G
Materials suitable for rooms subject to medium-heavy abrasion, such as detached houses and light-traffic commercial buildings.

H
Materials suitable for situations of relatively hard abrasion in environments without protection against scratching, both public and private.

Variazioni cromatiche

V0
Monochromatic - V0: tiles of the same shade are very uniform, in just one colour

V1
Uniform appearance - V1: uniform colour with only minimal differences between tiles in the same production run

V2
Slight variation - V2: clearly distinguishable differences in texture and pattern within the same production run

V3
Moderate variation - V3: significant variation in texture, pattern and colour from tile to tile within the same production run. The colour range should be viewed before selecting the material

V4
Substantial/random variation - V4: random differences from tile to tile. One tile may have totally different texture and colour from another. The colour range should be viewed before selecting the material

Certificazioni



ISO 14001



LEED Credits



CE 001MRZI



ISO 9001



FDES



UKCA
001MRZUK



Green Building
Council



Red List
Free
Declare.

Declare



SASO



GPP



HPD



EPD Italy



CAM Sassuolo



ISO 17889-1



CCC

© Copyright by Marazzi Group S.r.l.
All rights reserved, Marazzi Group Srl a Socio Unico
Viale Regina Pacis, 39 41049 Sassuolo (MO) Italy
T +39 0536 860800 F +39 0536 860644
info@marazzi.it www.marazzi.it

La riproduzione dei colori è approssimativa. Le tabelle con i dati riferiti ai contenuti per scatole ed ai pesi degli imballi sono aggiornate al momento della stampa del catalogo, pertanto i dati elencati possono subire variazioni.

Marazzi Group ha la facoltà esclusiva di modificare e sostituire, anche solo parzialmente i componenti dei sistemi illustrati in questo folder, senza l'obbligo di darne preavviso.



MARAZZI