

CONCRETE LOOK

Slow Cold



MARAZZI



Slow Cold

Matter becomes calm and sophisticated in surfaces that combine concrete with the charm of pressed earth, shaped by an essential, refined contemporary language. Slow Cold comes in sizes 75x75, 120x120, 75x150, 60x60 and 60x120, in Cemento, Salvia, Piombo, Gesso, Nebbia and Cromo. The Trama decor and Triangolo mosaic broaden the compositional possibilities. Designed for indoor and outdoor spaces, the collection is available in a 20mm version for outdoor use.



MPF1 Slow Cold Nebbia Mosaico Triangolo Rt 29x39cm
MPFO Slow Cold Gesso Mosaico Triangolo Rt 29x39cm
MPEU Slow Cold Nebbia R10 Rt 60x120cm
MJWZ Grande Stone Look Berici Bianco Satin 3D Ink Rt 6Mm 160x320cm



MPF1 Slow Cold Nebbia Mosaico Triangolo Rt 29x39cm
MPFO Slow Cold Gesso Mosaico Triangolo Rt 29x39cm
MPEU Slow Cold Nebbia R10 Rt 60x120cm
MJWZ Grande Stone Look Berici Bianco Satin 3D Ink Rt 6Mm 160x320cm



MPFG Slow Cold Gesso Decoro Trama Rt 75x75cm
MPE1 Slow Cold Gesso Rt 75x150cm



MPDS Slow Cold Salvia Strutturato Rt 120x120cm
MGUD Artcraft Pomice Struttura 3D Bande 20x20cm



MP9D Lume Off White Struttura 3D Rake Lux 6x24cm
MA9P Lume Off White Lux 6x24cm

MPDV Slow Cold Cromo Strutturato Rt 120x120cm
MPCM Slow Cold Cromo Rt 120x120cm






Slow Cold Index


Slow Cold

- Colorbody Fine Porcelain Stoneware



Cemento

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
120x120cm	Natural	MPCH	Slow Cold Cemento R10 Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R10B	> 0.40	Class 2	36+ Slider 96	P3	>= 0.42	H	V2	1	1,44	31,56	36	51,84	1.136,09
120x120cm	Natural	MPCR	Slow Cold Cemento Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1		P2	>= 0.42	H	V2	1	1,44	28,66	36	51,84	1.031,85
120x120cm	Structured Surface	MPDT	Slow Cold Cemento Strutturato Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R11B	> 0.40	Class 3	36+ Slider 96	P4	>= 0.42	H	V2	1	1,44	31,56	36	51,84	1.136,09
75x150cm	Natural	MPDZ	Slow Cold Cemento Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1		P2	>= 0.42	H	V2	2	2,25	44,01	21	47,25	924,30
75x75cm	Natural	MPE3	Slow Cold Cemento Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1		P2	>= 0.42	H	V2	2	1,13	21,46	42	47,25	901,37
60x60cm	Natural	MPEF	Slow Cold Cemento Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1		P2	>= 0.42	H	V2	3	1,08	21,58	40	43,20	863,31
60x60cm	Natural	MPER	Slow Cold Cemento R10 Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R10B	> 0.40	Class 2	36+ Slider 96	P3	>= 0.42	H	V2	3	1,08	22,00	40	43,20	880,02
60x120cm	Natural	MPE9	Slow Cold Cemento Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 2		P2	>= 0.42	H	V2	2	1,44	28,92	36	51,84	1.041,17
60x120cm	Natural	MPET	Slow Cold Cemento R10 Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R10B	> 0.40	Class 2	36+ Slider 96	P3	>= 0.42	H	V2	2	1,44	29,45	36	51,84	1.060,34




Cromo

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
120x120cm	Natural	MPCJ	Slow Cold Cromo R10 Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R10B	> 0.40	Class 2	36+ Slider 96	P3	>= 0.42	H	V2	1	1,44	31,56	36	51,84	1.136,09
120x120cm	Natural	MPCM	Slow Cold Cromo Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1		P2	>= 0.42	H	V2	1	1,44	32,00	36	51,84	1.152,00
120x120cm	Structured Surface	MPDV	Slow Cold Cromo Strutturato Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R11B	> 0.40	Class 3	36+ Slider 96	P4	>= 0.42	H	V2	1	1,44	31,56	36	51,84	1.136,09
75x150cm	Natural	MPDX	Slow Cold Cromo Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1		P2	>= 0.42	H	V2	2	2,25	44,20	21	47,25	928,29
75x75cm	Natural	MPE6	Slow Cold Cromo Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1		P2	>= 0.42	H	V2	2	1,13	22,62	42	47,25	949,94
60x60cm	Natural	MPEL	Slow Cold Cromo Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1		P2	>= 0.42	H	V2	3	1,08	21,14	40	43,20	845,73
60x60cm	Natural	MPES	Slow Cold Cromo R10 Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R10B	> 0.40	Class 2	36+ Slider 96	P3	>= 0.42	H	V2	3	1,08	20,86	40	43,20	834,30
60x120cm	Natural	MPEE	Slow Cold Cromo Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 2		P2	>= 0.42	H	V2	2	1,44	28,45	36	51,84	1.024,10
60x120cm	Natural	MPEX	Slow Cold Cromo R10 Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R10B	> 0.40	Class 2	36+ Slider 96	P3	>= 0.42	H	V2	2	1,44	29,42	36	51,84	1.059,26




Gesso

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
120x120cm	Natural	MPCG	Slow Cold Gesso R10 Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R10B	> 0.40	Class 2	36+ Slider 96	P3	>= 0.42	H	V2	1	1,44	31,56	36	51,84	1.136,09
120x120cm	Natural	MPCQ	Slow Cold Gesso Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1		P2	>= 0.42	H	V2	1	1,44	29,56	36	51,84	1.064,26
120x120cm	Structured Surface	MPCT	Slow Cold Gesso Strutturato Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R11B	> 0.40	Class 3	36+ Slider 96	P4	>= 0.42	H	V2	1	1,44	31,56	36	51,84	1.136,09
75x150cm	Natural	MPE1	Slow Cold Gesso Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1		P2	>= 0.42	H	V2	2	2,25	43,67	21	47,25	917,12
75x75cm	Natural	MPE4	Slow Cold Gesso Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1		P2	>= 0.42	H	V2	2	1,13	21,49	42	47,25	902,58
60x60cm	Natural	MPEG	Slow Cold Gesso Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1		P2	>= 0.42	H	V2	3	1,08	21,77	40	43,20	870,97
60x60cm	Natural	MPEM	Slow Cold Gesso R10 Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R10B	> 0.40	Class 2	36+ Slider 96	P3	>= 0.42	H	V2	3	1,08	21,70	40	43,20	868,17
60x120cm	Natural	MPEC	Slow Cold Gesso Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 2		P2	>= 0.42	H	V2	2	1,44	29,29	36	51,84	1.054,52
60x120cm	Natural	MPEV	Slow Cold Gesso R10 Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R10B	> 0.40	Class 2	36+ Slider 96	P3	>= 0.42	H	V2	2	1,44	29,47	36	51,84	1.060,77




Nebbia

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
120x120cm	Natural	MPCK	Slow Cold Nebbia R10 Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R10B	> 0.40	Class 2	36+ Slider 96	P3	>= 0.42	H	V2	1	1,44	31,56	36	51,84	1.136,09
120x120cm	Natural	MPCS	Slow Cold Nebbia Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1		P2	>= 0.42	H	V2	1	1,44	29,54	36	51,84	1.063,60
120x120cm	Structured Surface	MPDR	Slow Cold Nebbia Strutturato Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R11B	> 0.40	Class 3	36+ Slider 96	P4	>= 0.42	H	V2	1	1,44	31,56	36	51,84	1.136,09
75x150cm	Natural	MPDY	Slow Cold Nebbia Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1		P2	>= 0.42	H	V2	2	2,25	45,34	21	47,25	952,05
75x75cm	Natural	MPE5	Slow Cold Nebbia Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1		P2	>= 0.42	H	V2	2	1,13	22,53	42	47,25	946,14
60x60cm	Natural	MPEJ	Slow Cold Nebbia Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1		P2	>= 0.42	H	V2	3	1,08	21,22	40	43,20	848,72
60x60cm	Natural	MPEN	Slow Cold Nebbia R10 Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R10B	> 0.40	Class 2	36+ Slider 96	P3	>= 0.42	H	V2	3	1,08	21,73	40	43,20	869,39
60x120cm	Natural	MPEA	Slow Cold Nebbia Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 2		P2	>= 0.42	H	V2	2	1,44	28,39	36	51,84	1.022,08
60x120cm	Natural	MPEU	Slow Cold Nebbia R10 Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R10B	> 0.40	Class 2	36+ Slider 96	P3	>= 0.42	H	V2	2	1,44	29,67	36	51,84	1.068,21



Piombo

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
120x120cm	Natural	MPCF	Slow Cold Piombo R10 Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R10B	> 0.40	Class 2	36+ Slider 96	P3	>= 0.42	H	V2	1	1,44	31,56	36	51,84	1.136,09
120x120cm	Natural	MPCN	Slow Cold Piombo Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1		P2	>= 0.42	H	V2	1	1,44	32,00	36	51,84	1.152,00
120x120cm	Structured Surface	MPDU	Slow Cold Piombo Strutturato Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R11B	> 0.40	Class 3	36+ Slider 96	P4	>= 0.42	H	V2	1	1,44	31,56	36	51,84	1.136,09
75x150cm	Natural	MPE0	Slow Cold Piombo Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1		P2	>= 0.42	H	V2	2	2,25	45,11	21	47,25	947,27
75x75cm	Natural	MPE2	Slow Cold Piombo Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1		P2	>= 0.42	H	V2	2	1,13	22,48	42	47,25	944,06
60x60cm	Natural	MPEK	Slow Cold Piombo Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1		P2	>= 0.42	H	V2	3	1,08	21,27	40	43,20	850,73
60x60cm	Natural	MPEQ	Slow Cold Piombo R10 Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R10B	> 0.40	Class 2	36+ Slider 96	P3	>= 0.42	H	V2	3	1,08	21,77	40	43,20	870,62
60x120cm	Natural	MPED	Slow Cold Piombo Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 2		P2	>= 0.42	H	V2	2	1,44	29,51	36	51,84	1.062,51
60x120cm	Natural	MPEY	Slow Cold Piombo R10 Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R10B	> 0.40	Class 2	36+ Slider 96	P3	>= 0.42	H	V2	2	1,44	29,32	36	51,84	1.055,59



Salvia

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
120x120cm	Natural	MPCL	Slow Cold Salvia R10 Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R10B	> 0.40	Class 2	36+ Slider 96	P3	>= 0.42	H	V2	1	1,44	31,56	36	51,84	1.136,09
120x120cm	Natural	MPCP	Slow Cold Salvia Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1		P2	>= 0.42	H	V2	1	1,44	32,00	36	51,84	1.152,00
120x120cm	Structured Surface	MPDS	Slow Cold Salvia Strutturato Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R11B	> 0.40	Class 3	36+ Slider 96	P4	>= 0.42	H	V2	1	1,44	31,56	36	51,84	1.136,09
75x150cm	Natural	MPDW	Slow Cold Salvia Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1		P2	>= 0.42	H	V2	2	2,25	43,68	21	47,25	917,30
75x75cm	Natural	MPE7	Slow Cold Salvia Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1		P2	>= 0.42	H	V2	2	1,13	23,00	42	47,25	965,86
60x60cm	Natural	MPEH	Slow Cold Salvia Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1		P2	>= 0.42	H	V2	3	1,08	21,74	40	43,20	869,74
60x60cm	Natural	MPEP	Slow Cold Salvia R10 Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R10B	> 0.40	Class 2	36+ Slider 96	P3	>= 0.42	H	V2	3	1,08	22,00	40	43,20	880,02
60x120cm	Natural	MPE8	Slow Cold Salvia Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 2		P2	>= 0.42	H	V2	2	1,44	29,25	36	51,84	1.053,02
60x120cm	Natural	MPEW	Slow Cold Salvia R10 Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R10B	> 0.40	Class 2	36+ Slider 96	P3	>= 0.42	H	V2	2	1,44	29,46	36	51,84	1.060,56



Trama

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
75x75cm	Natural	MPFC	Slow Cold Piombo Decoro Trama Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink	R10	> 0.40	Class 1			>= 0.42	H	V2	2	1,13	23,00	42	47,25	965,96
75x75cm	Natural	MPFD	Slow Cold Nebbia Decoro Trama Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink	R10	> 0.40	Class 1			>= 0.42	H	V2	2	1,13	23,00	42	47,25	965,96
75x75cm	Natural	MPFE	Slow Cold Cemento Decoro Trama Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink	R10	> 0.40	Class 1			>= 0.42	H	V2	2	1,13	23,00	42	47,25	965,96
75x75cm	Natural	MPFF	Slow Cold Cromo Decoro Trama Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink	R10	> 0.40	Class 1			>= 0.42	H	V2	2	1,13	23,00	42	47,25	965,96
75x75cm	Natural	MPFG	Slow Cold Gesso Decoro Trama Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink	R10	> 0.40	Class 1			>= 0.42	H	V2	2	1,13	23,00	42	47,25	965,96
75x75cm	Natural	MPFH	Slow Cold Salvia Decoro Trama Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink	R10	> 0.40	Class 1			>= 0.42	H	V2	2	1,13	23,00	42	47,25	965,96



Mosaico Triangolo Cemento

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
29x39cm	Natural	MPF3	Slow Cold Cemento Mosaico Triangolo Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall									V2	4	0,45	15,00	50	22,62	749,99




Mosaico Triangolo Salvia

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
29x39cm	Natural	MPF2	Slow Cold Salvia Mosaico Triangolo Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall									V2	4	0,45	15,00	50	22,62	749,99



Mosaico Triangolo Piombo

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
29x39cm	Natural	MPF4	Slow Cold Piombo Mosaico Triangolo Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall									V2	4	0,45	15,00	50	22,62	749,99



Mosaico Triangolo Gesso

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
29x39cm	Natural	MPF0	Slow Cold Gesso Mosaico Triangolo Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall									V2	4	0,45	15,00	50	22,62	749,99



Mosaico Triangolo Nebbia

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
29x39cm	Natural	MPF1	Slow Cold Nebbia Mosaico Triangolo Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall									V2	4	0,45	15,00	50	22,62	749,99



Mosaico Triangolo Cromo

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
29x39cm	Natural	MPEZ	Slow Cold Cromo Mosaico Triangolo Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall									V2	4	0,45	15,00	50	22,62	749,99

Legenda

Destinazioni d'uso

D
Tiles suitable only for residential bathrooms and bedrooms; any type of abrasion must be avoided.

E
Tiles suitable for any room of a house except for entrance areas and kitchens. Low stress abrasive wear.

F
Tiles suitable for any room of a house without direct access from the outside or access not protected by doormats. Average stress abrasive wear.

G
Materials suitable for rooms subject to medium-heavy abrasion, such as detached houses and light-traffic commercial buildings.

H
Materials suitable for situations of relatively hard abrasion in environments without protection against scratching, both public and private.

Variazioni cromatiche

V0
Monochromatic - V0: tiles of the same shade are very uniform, in just one colour























V1
Uniform appearance - V1: uniform colour with only minimal differences between tiles in the same production run

V2
Slight variation - V2: clearly distinguishable differences in texture and pattern within the same production run

V3
Moderate variation - V3: significant variation in texture, pattern and colour from tile to tile within the same production run. The colour range should be viewed before selecting the material

V4
Substantial/random variation - V4: random differences from tile to tile. One tile may have totally different texture and colour from another. The colour range should be viewed before selecting the material

Certificazioni

					
ISO 14001	ISO 50001	ISO 45001	ISO 9001	Green Building Council	GPP
					
EPD Italy	ISO 17889-1	Greenguard Certification	LEED Credits	FDES	Declare
					
HPD	CAM Sassuolo	CAM Casiglie	CCC	CAM Fiorano	CE 001MRZI
					
CE 009MRZI	UKCA 001MRZUK	UKCA 009MRZUK	SASO		

© Copyright by Marazzi Group S.r.l.
All rights reserved, Marazzi Group Srl a Socio Unico
Viale Regina Pacis, 39 41049 Sassuolo (MO) Italy
T +39 0536 860800 F +39 0536 860644
info@marazzi.it www.marazzi.it

La riproduzione dei colori è approssimativa. Le tabelle con i dati riferiti ai contenuti per scatole ed ai pesi degli imballi sono aggiornate al momento della stampa del catalogo, pertanto i dati elencati possono subire variazioni.

Marazzi Group ha la facoltà esclusiva di modificare e sostituire, anche solo parzialmente i componenti dei sistemi illustrati in questo folder, senza l'obbligo di darne preavviso.



MARAZZI