

CONCRETE LOOK

Slow



MARAZZI

Slow

Slow rediscovers the warmth of cotto through soft, textured surfaces for coordinated indoor and outdoor settings, expressed with a welcoming, contemporary character. The collection comes in 60x60, 60x120, 75x75, 120x120 and 75x150 formats, in Sabbia, Argilla, Cotto, Calce, Pomice and Coccio. Rafia and Tapis decors, with the Circolare mosaic, expand the compositional possibilities for warm, natural projects. It is also available in a 20mm version for outdoor use.



MGU3 Artcraft Cotto 5x30cm
MGJS Grande Resin Look Rosa Antico Satin Rt 120x278cm
MGFS Grande Marble Look Patagonia Lux Rt 6Mm 160x320cm
MGDM Grande Marble Look Taj Mahal Satin Rt 6Mm 160x320cm



MP2Y Slow Calce Mosaico Circolare Rt 32x41cm
MNEC Slow Calce Rt 75x150cm



MFSX Slow Coccio Strutturato 60x60cm



MGUH Artcraft Sabbia Struttura 3D Bande 20x20cm
MGSQ Artcraft Coccio 20x20cm
MFS6 Slow Coccio Rt 60x120cm



MH9D Artcraft Decoro Segni B Semimatt 20x20cm
MFSX Slow Coccio Strutturato 60x60cm



MGSQ Artcraft Coccio 20x20cm
MFS6 Slow Coccio Rt 60x120cm

MGUH Artcraft Sabbia Struttura 3D Bande 20x20cm



MKGU Slow Pomice Decoro Rafia Rt 75x75cm
MGUA Artcraft Bianco Semimatt 5x30cm



MFKE Slow Pomice Rt 120x120cm



MKGV Slow Calce Decoro Rafia Rt 75x75cm



MKGU Slow Pomice Decoro Rafia Rt 75x75cm
MFZW Slow Sabbia Strutturato 120x120cm



MGSS Artcraft Cotto 20x20cm
MFPT Slow Cotto Rt 75x75cm



MM6Z Slow Coccio Decoro Tapis Rt 60x120cm
MGTL Artcraft Coccio 5x30cm



MFSG Slow Calce Rt 60x60cm







Slow Index

MGU3 Artcraft Cotto 5x30cm
MGJS Grande Resin Look Rosa Antico Satin Rt 120x278cm
MGFS Grande Marble Look Patagonia Lux Rt 6Mm 160x320cm
MGDM Grande Marble Look Taj Mahal Satin Rt 6Mm 160x320cm

Slow

- Colorbody Fine Porcelain Stoneware



Argilla

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
120x120cm	Natural	MFKV	Slow Argilla Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	1	1,44	31,56	36	51,84	1.136,09
75x75cm	Natural	MFRS	Slow Argilla Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	2	1,13	20,85	42	47,25	875,65
60x120cm	Natural	MFSC	Slow Argilla Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	2	1,44	30,23	36	51,84	1.088,39
60x60cm	Natural	MFSR	Slow Argilla Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	3	1,08	21,79	40	43,20	871,49
60x60cm	Structured Surface	MFUS	Slow Argilla Strutturato	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R11B	> 0.40	Class 3	36+ Slider 96		>= 0.42	H	V2	3	1,08	22,50	40	43,20	900,00
75x150cm	Natural	MNE2	Slow Argilla Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	2	2,25	48,41	21	47,25	1.016,57



Calce

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
120x120cm	Natural	MFKG	Slow Calce Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	1	1,44	30,09	36	51,84	1.083,39
120x120cm	Structured Surface	MFZS	Slow Calce Strutturato	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R11B	> 0.40	Class 3	36+ Slider 96		>= 0.42	H	V2	1	1,44	30,51	36	51,84	1.098,30
75x75cm	Natural	MFNC	Slow Calce Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	2	1,13	21,32	42	47,25	895,56
60x120cm	Natural	MFS2	Slow Calce Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	2	1,44	29,21	36	51,84	1.051,52
60x60cm	Natural	MFSG	Slow Calce Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	3	1,08	22,36	40	43,20	894,60
60x60cm	Structured Surface	MFSU	Slow Calce Strutturato	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R11B	> 0.40	Class 3	36+ Slider 96		>= 0.42	H	V2	3	1,08	21,91	40	43,20	876,45
75x150cm	Natural	MNEC	Slow Calce Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	2	2,25	44,76	21	47,25	939,92



Coccio

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
120x120cm	Natural	MFKR	Slow Coccio Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	1	1,44	28,64	36	51,84	1.031,03
120x120cm	Structured Surface	MG01	Slow Coccio Strutturato	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R11B	> 0.40	Class 3	36+ Slider 96		>= 0.42	H	V2	1	1,44	29,54	36	51,84	1.063,60
75x75cm	Natural	MFNU	Slow Coccio Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	2	1,13	22,79	42	47,25	957,25
60x120cm	Natural	MFS6	Slow Coccio Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	2	1,44	29,61	36	51,84	1.066,01
60x60cm	Natural	MFSL	Slow Coccio Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	3	1,08	22,14	40	43,20	885,79
60x60cm	Structured Surface	MFSX	Slow Coccio Strutturato	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R11B	> 0.40	Class 3	36+ Slider 96		>= 0.42	H	V2	3	1,08	22,00	40	43,20	880,02
75x150cm	Natural	MNDV	Slow Coccio Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	2	2,25	45,56	21	47,25	956,67



Cotto

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
120x120cm	Natural	MFKP	Slow Cotto Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	1	1,44	29,27	36	51,84	1.053,66
75x75cm	Natural	MFPT	Slow Cotto Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	2	1,13	22,85	42	47,25	959,59
60x120cm	Natural	MFS8	Slow Cotto Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	2	1,44	29,65	36	51,84	1.067,33
60x60cm	Natural	MFSN	Slow Cotto Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	3	1,08	21,79	40	43,20	871,49
60x60cm	Structured Surface	MFSZ	Slow Cotto Strutturato	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R11B	> 0.40	Class 3	36+ Slider 96		>= 0.42	H	V2	3	1,08	22,02	40	43,20	880,91
75x150cm	Natural	MNE3	Slow Cotto Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	2	2,25	46,28	21	47,25	971,82
120x120cm	Structured Surface	MP3J	Slow Cotto Strutturato Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R11B	> 0.40	Class 3	36+ Slider 96		>= 0.42	H	V2	1	1,44	28,98	36	51,84	1.043,27



Pomice

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
120x120cm	Natural	MFKE	Slow Pomice Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	1	1,44	28,57	36	51,84	1.028,37
75x75cm	Natural	MFN3	Slow Pomice Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	2	1,13	20,94	42	47,25	879,56
60x120cm	Natural	MFS1	Slow Pomice Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	2	1,44	29,20	36	51,84	1.051,09
60x60cm	Natural	MFSE	Slow Pomice Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	3	1,08	21,86	40	43,20	874,32
60x60cm	Structured Surface	MFST	Slow Pomice Strutturato	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R11B	> 0.40	Class 3	36+ Slider 96		>= 0.42	H	V2	3	1,08	22,58	40	43,20	903,39
75x150cm	Natural	MNE1	Slow Pomice Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	2	2,25	43,07	21	47,25	904,48
120x120cm	Structured Surface	MP3H	Slow Pomice Strutturato Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R11B	> 0.40	Class 3	36+ Slider 96		>= 0.42	H	V2	1	1,44	29,13	36	51,84	1.048,54



Sabbia

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
120x120cm	Natural	MFKM	Slow Sabbia Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	1	1,44	29,78	36	51,84	1.072,18
120x120cm	Structured Surface	MFZW	Slow Sabbia Strutturato	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R11B	> 0.40	Class 3	36+ Slider 96		>= 0.42	H	V2	1	1,44	31,56	36	51,84	1.136,09
75x75cm	Natural	MFNS	Slow Sabbia Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	2	1,13	22,84	42	47,25	959,20
60x120cm	Natural	MFS4	Slow Sabbia Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	2	1,44	28,91	36	51,84	1.040,76
60x60cm	Natural	MFSJ	Slow Sabbia Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	3	1,08	22,59	40	43,20	903,58
60x60cm	Structured Surface	MFSV	Slow Sabbia Strutturato	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R11B	> 0.40	Class 3	36+ Slider 96		>= 0.42	H	V2	3	1,08	22,76	40	43,20	910,24
75x150cm	Natural	MNDU	Slow Sabbia Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, High Performance	R9	> 0.40	Class 1			>= 0.42	H	V2	2	2,25	46,56	21	47,25	977,86




Rafia

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
75x75cm	Natural	MKGU	Slow Pomice Decoro Rafia Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, Touch	R10B > 0.40		Class 1			>= 0.42	H	V2	2	1,13	22,22	42	47,25	933,33
75x75cm	Natural	MKGV	Slow Calce Decoro Rafia Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, Touch	R10B > 0.40		Class 1			>= 0.42	H	V2	2	1,13	22,22	42	47,25	933,33
75x75cm	Natural	MKGW	Slow Sabbia Decoro Rafia Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, Touch	R10B > 0.40		Class 1			>= 0.42	H	V2	2	1,13	22,22	42	47,25	933,33
75x75cm	Natural	MKGY	Slow Coccio Decoro Rafia Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, Touch	R10B > 0.40		Class 1			>= 0.42	H	V2	2	1,13	22,22	42	47,25	933,33
75x75cm	Natural	MKGZ	Slow Cotto Decoro Rafia Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, Touch	R10B > 0.40		Class 1			>= 0.42	H	V2	2	1,13	22,22	42	47,25	933,33
75x75cm	Natural	MKH1	Slow Argilla Decoro Rafia Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, Touch	R10B > 0.40		Class 1			>= 0.42	H	V2	2	1,13	22,22	42	47,25	933,33




Tapis

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
60x120cm	Natural	MM6R	Slow Pomice Decoro Tapis Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, Touch	R10B > 0.40		Class 1				H	V2	2	1,44	28,57	36	51,84	1.028,57
60x120cm	Natural	MM6V	Slow Calce Decoro Tapis Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, Touch	R10B > 0.40		Class 1				H	V2	2	1,44	28,57	36	51,84	1.028,57
60x120cm	Natural	MM6W	Slow Sabbia Decoro Tapis Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, Touch	R10B > 0.40		Class 1				H	V2	2	1,44	28,57	36	51,84	1.028,57
60x120cm	Natural	MM6Z	Slow Coccio Decoro Tapis Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, Touch	R10B > 0.40		Class 1				H	V2	2	1,44	30,00	36	51,84	1.079,95
60x120cm	Natural	MM70	Slow Cotto Decoro Tapis Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, Touch	R10B > 0.40		Class 1				H	V2	2	1,44	33,33	36	51,84	1.200,00
60x120cm	Natural	MM7S	Slow Argilla Decoro Tapis Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall	3D Ink, Touch	R10B > 0.40		Class 1				H	V2	2	1,44	28,57	36	51,84	1.028,57




Mosaic Circolare Sabbia

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
32,1x41,6cm	Natural	MP2X	Slow Sabbia Mosaico Circolare Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall									V2	4	0,44	9,00	50	22,00	450,00




Mosaic Circolare Argilla

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
32,1x41,6cm	Natural	MP2U	Slow Argilla Mosaico Circolare Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall									V2	4	0,44	9,00	50	22,00	450,00



Mosaic Circolare Cotto

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
32,1x41,6cm	Natural	MP2Z	Slow Cotto Mosaico Circolare Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall									V2	4	0,44	9,00	50	22,00	450,00




Mosaic Circolare Calce

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
32,1x41,6cm	Natural	MP2Y	Slow Calce Mosaico Circolare Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall									V2	4	0,44	9,00	50	22,00	450,00



Mosaic Circolare Pomice

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
32,1x41,6cm	Natural	MP2T	Slow Pomice Mosaico Circolare Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall									V2	4	0,44	9,00	50	22,00	450,00



Mosaic Circolare Coccio

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
32,1x41,6cm	Natural	MP2V	Slow Coccio Mosaico Circolare Rt	MM 09	.	Frost proof, Resistance deep abrasion	Floor & Wall									V2	4	0,44	9,00	50	22,00	450,00

Legenda

Destinazioni d'uso

D
Tiles suitable only for residential bathrooms and bedrooms; any type of abrasion must be avoided.

E
Tiles suitable for any room of a house except for entrance areas and kitchens. Low stress abrasive wear.

F
Tiles suitable for any room of a house without direct access from the outside or access not protected by doormats. Average stress abrasive wear.

G
Materials suitable for rooms subject to medium-heavy abrasion, such as detached houses and light-traffic commercial buildings.

H
Materials suitable for situations of relatively hard abrasion in environments without protection against scratching, both public and private.

Variazioni cromatiche

V0
Monochromatic - V0: tiles of the same shade are very uniform, in just one colour

V1
Uniform appearance - V1: uniform colour with only minimal differences between tiles in the same production run

V2
Slight variation - V2: clearly distinguishable differences in texture and pattern within the same production run

V3
Moderate variation - V3: significant variation in texture, pattern and colour from tile to tile within the same production run. The colour range should be viewed before selecting the material

V4
Substantial/random variation - V4: random differences from tile to tile. One tile may have totally different texture and colour from another. The colour range should be viewed before selecting the material

Certificazioni



ISO 14001



ISO 50001



ISO 45001



ISO 9001



Green Building Council



GPP



EPD Italy



ISO 17889-1



Recycled Material



Greenguard Certification



LEED Credits



QBUPEC



QBUPEC D+



FDES



Declare



HPD



CAM Sassuolo



CAM Casiglie



CCC



CAM Fiorano



CE 001MRZI



CE 009MRZI



UKCA 001MRZUK



UKCA 009MRZUK



SASO

© Copyright by Marazzi Group S.r.l., 2023.
All rights reserved, Marazzi Group Srl a Socio Unico
Viale Regina Pacis, 39 41049 Sassuolo (MO) Italy
T +39 0536 860800 F +39 0536 860644
info@marazzi.it www.marazzi.it

La riproduzione dei colori è approssimativa. Le tabelle con i dati riferiti ai contenuti per scatole ed ai pesi degli imballi sono aggiornate al momento della stampa del catalogo, pertanto i dati elencati possono subire variazioni.

Marazzi Group ha la facoltà esclusiva di modificare e sostituire, anche solo parzialmente i componenti dei sistemi illustrati in questo folder, senza l'obbligo di darne preavviso.



MARAZZI