

FLOORS 20 MM

# Cementum20



MARAZZI

# Cementum20

From concrete takes shape Cementum20, an outdoor porcelain stoneware collection with a material and contemporary character. In Sand, Ash, Nickel and Lead, in sizes 60x60, 60x120 and 120x120, it creates a balanced and realistic surface. The cast-concrete look expresses depth and restraint. Tecnico technology ensures resistance and reliability. Designed for outdoor spaces, it interprets terraces, walkways and demanding high-use settings with natural, lasting ease.



MQ7W Lume Green Lux 10x10cm  
M9YW Cementum20 Ash Rt 60x120cm  
M9SK Cementum Ash Rt 60x120cm







# Cementum20 Index

MQ7W Lume Green Lux 10x10cm  
M9YW Cementum20 Ash Rt 60x120cm  
M9SK Cementum Ash Rt 60x120cm

# Cementum20

- Colorbody Fine Porcelain Stoneware · Porcelain Stoneware



## Ash

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
60x120cm	Structured Surface	M9YW	Cementum20 Ash Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V2	1	0,72	32,52	36	25,92	1.170,73	
60x60cm	Structured Surface	MPMR	Cementum20 Ash Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor		R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V2	2	0,72	32,58	32	23,04	1.042,53	



## Lead

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
60x120cm	Structured Surface	M9YZ	Cementum20 Lead Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V2	1	0,72	32,09	36	25,92	1.155,08	
60x60cm	Structured Surface	MPMS	Cementum20 Lead Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor		R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V2	2	0,72	31,90	32	23,04	1.020,82	



## Nickel

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
60x120cm	Structured Surface	M9YY	Cementum20 Nickel Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V2	1	0,72	32,67	36	25,92	1.176,04	
120x120cm	Structured Surface	MFFS	Cementum20 Nickel Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V2	1	1,44	62,02	18	25,92	1.116,28	
60x60cm	Structured Surface	MPMU	Cementum20 Nickel Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor		R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V2	2	0,72	33,03	32	23,04	1.056,88	



## Sand

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
60x120cm	Structured Surface	M9YX	Cementum20 Sand Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V2	1	0,72	32,39	36	25,92	1.165,99	
60x60cm	Structured Surface	MPMT	Cementum20 Sand Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor		R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V2	2	0,72	32,32	32	23,04	1.034,11	

# Legenda

## Destinazioni d'uso

**D**  
Tiles suitable only for residential bathrooms and bedrooms; any type of abrasion must be avoided.

**E**  
Tiles suitable for any room of a house except for entrance areas and kitchens. Low stress abrasive wear.

**F**  
Tiles suitable for any room of a house without direct access from the outside or access not protected by doormats. Average stress abrasive wear.

**G**  
Materials suitable for rooms subject to medium-heavy abrasion, such as detached houses and light-traffic commercial buildings.

**H**  
Materials suitable for situations of relatively hard abrasion in environments without protection against scratching, both public and private.

## Variazioni cromatiche

**V0**  
Monochromatic - V0: tiles of the same shade are very uniform, in just one colour

**V1**  
Uniform appearance - V1: uniform colour with only minimal differences between tiles in the same production run

**V2**  
Slight variation - V2: clearly distinguishable differences in texture and pattern within the same production run

**V3**  
Moderate variation - V3: significant variation in texture, pattern and colour from tile to tile within the same production run. The colour range should be viewed before selecting the material

**V4**  
Substantial/random variation - V4: random differences from tile to tile. One tile may have totally different texture and colour from another. The colour range should be viewed before selecting the material

# Certificazioni



ISO 14001



ISO 45001



ISO 9001



Green Building Council



GPP



EPD Italy



ISO 17889-1



Greenguard Certification



LEED Credits



QBUPEC F+



FDES



Declare



HPD



CAM Sassuolo



CAM Casiglie



CCC



CE 001MRZI



UKCA 001MRZUK



SASO

© Copyright by Marazzi Group S.r.l., 2023.  
All rights reserved, Marazzi Group Srl a Socio Unico  
Viale Regina Pacis, 39 41049 Sassuolo (MO) Italy  
T +39 0536 860800 F +39 0536 860644  
info@marazzi.it www.marazzi.it

La riproduzione dei colori è approssimativa. Le tabelle con i dati riferiti ai contenuti per scatole ed ai pesi degli imballi sono aggiornate al momento della stampa del catalogo, pertanto i dati elencati possono subire variazioni.

Marazzi Group ha la facoltà esclusiva di modificare e sostituire, anche solo parzialmente i componenti dei sistemi illustrati in questo folder, senza l'obbligo di darne preavviso.



**MARAZZI**