

FLOORS 20 MM

# Mystone Berici20



MARAZZI

# Mystone Berici20

Designed for outdoor spaces, Mystone Berici 20 interprets Vicenza stone in a high thickness solution with a natural and contemporary aesthetic. The porcelain stoneware is available in Bianco, Grigio, Beige and Cenere in the 60x120 size with outdoor surface. Installation can be carried out with adhesive or on gravel to ensure design flexibility. Tecnico technology ensures resistance and reliability in all residential, commercial and outdoor design settings.





# Mystone Berici20 Index

**MP17** Mystone Berici20 Beige Elemento L Rt 15x120cm  
**MMDO** Mystone Berici20 Beige Strutturato 60x120cm


# Mystone Berici20

- Colorbody Fine Porcelain Stoneware




## Beige

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
60x120cm	Structured Surface	MMD0	Mystone Berici20 Beige Strutturato	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96	P4	>= 0.60	H	V2	1	0,72	32,54	36	25,92	1.171,26




## Bianco

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
60x120cm	Structured Surface	MMCZ	Mystone Berici20 Bianco Strutturato	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96	P4	>= 0.60	H	V2	1	0,72	32,32	36	25,92	1.163,38



## Cenere

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
60x120cm	Structured Surface	MMD2	Mystone Berici20 Cenere Strutturato	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96	P4	>= 0.60	H	V2	1	0,72	32,04	36	25,92	1.153,54



## Grigio

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
60x120cm	Structured Surface	MMD1	Mystone Berici20 Grigio Strutturato	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96	P4	>= 0.60	H	V2	1	0,72	32,09	36	25,92	1.155,08

# Legenda

## Destinazioni d'uso

**D**  
Tiles suitable only for residential bathrooms and bedrooms; any type of abrasion must be avoided.

**E**  
Tiles suitable for any room of a house except for entrance areas and kitchens. Low stress abrasive wear.

**F**  
Tiles suitable for any room of a house without direct access from the outside or access not protected by doormats. Average stress abrasive wear.

**G**  
Materials suitable for rooms subject to medium-heavy abrasion, such as detached houses and light-traffic commercial buildings.

**H**  
Materials suitable for situations of relatively hard abrasion in environments without protection against scratching, both public and private.

## Variazioni cromatiche

**V0**  
Monochromatic - V0: tiles of the same shade are very uniform, in just one colour

**V1**  
Uniform appearance - V1: uniform colour with only minimal differences between tiles in the same production run

**V2**  
Slight variation - V2: clearly distinguishable differences in texture and pattern within the same production run

**V3**  
Moderate variation - V3: significant variation in texture, pattern and colour from tile to tile within the same production run. The colour range should be viewed before selecting the material

**V4**  
Substantial/random variation - V4: random differences from tile to tile. One tile may have totally different texture and colour from another. The colour range should be viewed before selecting the material

# Certificazioni



ISO 14001



Greenguard Certification



CAM Sassuolo



ISO 9001



LEED Credits



CCC



Green Building Council



QBUPEC F+



CE 001MRZI



GPP



FDES



UKCA 001MRZUK



EPD Italy



Declare



SASO



ISO 17889-1



HPD

© Copyright by Marazzi Group S.r.l., 2023.  
All rights reserved, Marazzi Group Srl a Socio Unico  
Viale Regina Pacis, 39 41049 Sassuolo (MO) Italy  
T +39 0536 860800 F +39 0536 860644  
info@marazzi.it www.marazzi.it

La riproduzione dei colori è approssimativa. Le tabelle con i dati riferiti ai contenuti per scatole ed ai pesi degli imballi sono aggiornate al momento della stampa del catalogo, pertanto i dati elencati possono subire variazioni.

Marazzi Group ha la facoltà esclusiva di modificare e sostituire, anche solo parzialmente i componenti dei sistemi illustrati in questo folder, senza l'obbligo di darne preavviso.



**MARAZZI**