

FLOORS 20 MM

Mystone Limestone20



MARAZZI



Mystone Limestone20

Limestone finds a contemporary expression in Mystone Limestone20, with natural, minimal graphics shaped by light inclusions and warm tones. In porcelain stoneware, it is available in Sand, Ivory and Taupe, in the 60x60, 60x120, 120x120 and 80x80 sizes. Tecnico technology improves reliability, grip and slip resistance. Designed for outdoor spaces, it brings balance, natural character and a refined presence to residential and commercial settings alike today.







Mystone Limestone20 Index

MPMQ Mystone Limestone20 Ivory Strutturato Rt 60x60cm
MP8Y Lume Bone Lux 6x24cm


Mystone Limestone20

- Colorbody Fine Porcelain Stoneware · Porcelain Stoneware




Ivory

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
80x80cm	Structured Surface	M7FK	Mystone Limestone20 Ivory Strutturato Rettificato	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V2	1	0,64	28,43	45	28,80	1.279,43	
60x120cm	Structured Surface	M7SS	Mystone Limestone20 Ivory Strutturato Rettificato	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V2	1	0,72	31,89	36	25,92	1.147,92	
120x120cm	Structured Surface	MFH3	Mystone Limestone20 Ivory Strutturato Rettificato	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V2	1	1,44	62,02	18	25,92	1.116,28	
60x60cm	Structured Surface	MPMQ	Mystone Limestone20 Ivory Strutturato Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor		R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V2	2	0,72	32,40	32	23,04	1.036,90	



Sand

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
80x80cm	Structured Surface	M7FJ	Mystone Limestone20 Sand Strutturato Rettificato	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V2	1	0,64	28,60	45	28,80	1.286,86	
60x120cm	Structured Surface	M7SR	Mystone Limestone20 Sand Strutturato Rettificato	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V2	1	0,72	32,32	36	25,92	1.163,38	
120x120cm	Structured Surface	MFH4	Mystone Limestone20 Sand Strutturato Rettificato	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V2	1	1,44	62,02	18	25,92	1.116,28	
60x60cm	Structured Surface	MPMP	Mystone Limestone20 Sand Strutturato Rt	MM 20	.	Frost proof, Resistance deep abrasion	Floor		R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V2	2	0,72	32,04	32	23,04	1.025,37	



Taupe

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
80x80cm	Structured Surface	M7FH	Mystone Limestone20 Taupe Strutturato Rettificato	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V2	1	0,64	28,62	45	28,80	1.288,01	
60x120cm	Structured Surface	M7SQ	Mystone Limestone20 Taupe Strutturato Rettificato	MM 20	.	Frost proof, Resistance deep abrasion	Floor	High Performance	R11C	> 0.40	Class 3	36+ Slider 96	>= 0.60	H	V2	1	0,72	32,10	36	25,92	1.155,60	

Legenda

Destinazioni d'uso

D
Tiles suitable only for residential bathrooms and bedrooms; any type of abrasion must be avoided.

E
Tiles suitable for any room of a house except for entrance areas and kitchens. Low stress abrasive wear.

F
Tiles suitable for any room of a house without direct access from the outside or access not protected by doormats. Average stress abrasive wear.

G
Materials suitable for rooms subject to medium-heavy abrasion, such as detached houses and light-traffic commercial buildings.

H
Materials suitable for situations of relatively hard abrasion in environments without protection against scratching, both public and private.

Variazioni cromatiche

V0
Monochromatic - V0: tiles of the same shade are very uniform, in just one colour

V1
Uniform appearance - V1: uniform colour with only minimal differences between tiles in the same production run

V2
Slight variation - V2: clearly distinguishable differences in texture and pattern within the same production run

V3
Moderate variation - V3: significant variation in texture, pattern and colour from tile to tile within the same production run. The colour range should be viewed before selecting the material

V4
Substantial/random variation - V4: random differences from tile to tile. One tile may have totally different texture and colour from another. The colour range should be viewed before selecting the material

Certificazioni



ISO 14001



ISO 45001



ISO 9001



Green Building Council



GPP



EPD Italy



ISO 17889-1



Greenguard Certification



LEED Credits



QBUPEC F+



FDES



Declare



HPD



CAM Sassuolo



CAM Casiglie



CCC



CE 001MRZI



UKCA 001MRZUK



SASO

© Copyright by Marazzi Group S.r.l.
All rights reserved, Marazzi Group Srl a Socio Unico
Viale Regina Pacis, 39 41049 Sassuolo (MO) Italy
T +39 0536 860800 F +39 0536 860644
info@marazzi.it www.marazzi.it

La riproduzione dei colori è approssimativa. Le tabelle con i dati riferiti ai contenuti per scatole ed ai pesi degli imballi sono aggiornate al momento della stampa del catalogo, pertanto i dati elencati possono subire variazioni.

Marazzi Group ha la facoltà esclusiva di modificare e sostituire, anche solo parzialmente i componenti dei sistemi illustrati in questo folder, senza l'obbligo di darne preavviso.



MARAZZI