

STONE LOOK

Pietra Occitana



MARAZZI



Pietra Occitana

Like a stone in dialogue with outdoor light, Pietra Occitana dresses exterior spaces with a natural, textured aesthetic. The porcelain stoneware collection comes in Bianco, Grigio, Beige and Antracite, in 20x20 and 20x40 sizes, for different laying solutions. Technology, practicality and design come together in a versatile, functional surface created exclusively to enhance terraces, walkways, courtyards and outdoor spaces with clear visual coherence and balance.



MH7C Pietra Occitana Beige 20x40cm
MH77 Pietra Occitana Beige 20x20cm



MH7C Pietra Occitana Beige 20x40cm
MH77 Pietra Occitana Beige 20x20cm



Pietra Occitana Index

MH7C Pietra Occitana Beige 20x40cm
MH77 Pietra Occitana Beige 20x20cm

Pietra Occitana

- Porcelain Stoneware



Antracite

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
20x20cm	Structured Surface	MH75	Pietra Occitana Antracite	MM 09		Frost proof, Resistance deep abrasion	Floor & Wall		R11B	> 0.40	Class 3	36+ Slider 96		>= 0.42	G	V3	26	1,04	17,65	54	56,16	953,16
20x40cm	Structured Surface	MH7E	Pietra Occitana Antracite	MM 09		Frost proof, Resistance deep abrasion	Floor & Wall		R11B	> 0.40	Class 3	36+ Slider 96		>= 0.42	G	V3	13	1,04	18,62	54	56,16	1.005,37




Beige

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
20x20cm	Structured Surface	MH77	Pietra Occitana Beige	MM 09		Frost proof, Resistance deep abrasion	Floor & Wall		R11B	> 0.40	Class 3	36+ Slider 96		>= 0.42	G	V3	26	1,04	18,21	54	56,16	983,37
20x40cm	Structured Surface	MH7C	Pietra Occitana Beige	MM 09		Frost proof, Resistance deep abrasion	Floor & Wall		R11B	> 0.40	Class 3	36+ Slider 96		>= 0.42	G	V3	13	1,04	18,29	54	56,16	987,69



Bianco

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
20x20cm	Structured Surface	MH76	Pietra Occitana Bianco	MM 09		Frost proof, Resistance deep abrasion	Floor & Wall		R11B	> 0.40	Class 3	36+ Slider 96		>= 0.42	G	V3	26	1,04	17,79	54	56,16	960,66
20x40cm	Structured Surface	MH7A	Pietra Occitana Bianco	MM 09		Frost proof, Resistance deep abrasion	Floor & Wall		R11B	> 0.40	Class 3	36+ Slider 96		>= 0.42	G	V3	13	1,04	18,87	54	56,16	1.019,05



Grigio

Formato	Superfici	Codice	Descrizione	Spessore	Rett.	Caratteristiche tecniche	Utilizzo	Premium Tech	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Pezzi per scatola	Mq	Kg	Scatole per pallet	Mq	Kg
20x20cm	Structured Surface	MH78	Pietra Occitana Grigio	MM 09		Frost proof, Resistance deep abrasion	Floor & Wall		R11B	> 0.40	Class 3	36+ Slider 96		>= 0.42	G	V3	26	1,04	19,30	54	56,16	1.042,32
20x40cm	Structured Surface	MH7D	Pietra Occitana Grigio	MM 09		Frost proof, Resistance deep abrasion	Floor & Wall		R11B	> 0.40	Class 3	36+ Slider 96		>= 0.42	G	V3	13	1,04	18,53	54	56,16	1.000,71

Legenda

Destinazioni d'uso

D
Tiles suitable only for residential bathrooms and bedrooms; any type of abrasion must be avoided.

E
Tiles suitable for any room of a house except for entrance areas and kitchens. Low stress abrasive wear.

F
Tiles suitable for any room of a house without direct access from the outside or access not protected by doormats. Average stress abrasive wear.

G
Materials suitable for rooms subject to medium-heavy abrasion, such as detached houses and light-traffic commercial buildings.

H
Materials suitable for situations of relatively hard abrasion in environments without protection against scratching, both public and private.

Variazioni cromatiche

V0
Monochromatic - V0: tiles of the same shade are very uniform, in just one colour

V1
Uniform appearance - V1: uniform colour with only minimal differences between tiles in the same production run

V2
Slight variation - V2: clearly distinguishable differences in texture and pattern within the same production run

V3
Moderate variation - V3: significant variation in texture, pattern and colour from tile to tile within the same production run. The colour range should be viewed before selecting the material

V4
Substantial/random variation - V4: random differences from tile to tile. One tile may have totally different texture and colour from another. The colour range should be viewed before selecting the material

Certificazioni



ISO 14001



EPD Italy



HPD



ISO 50001



ISO 17889-1



CAM Sassuolo



ISO 45001



Greenguard Certification



CAM Fiorano



ISO 9001



LEED Credits



CE 001MRZI



Green Building Council



FDES



UKCA 001MRZUK



GPP



Declare

© Copyright by Marazzi Group S.r.l.
All rights reserved, Marazzi Group Srl a Socio Unico
Viale Regina Pacis, 39 41049 Sassuolo (MO) Italy
T +39 0536 860800 F +39 0536 860644
info@marazzi.it www.marazzi.it

La riproduzione dei colori è approssimativa. Le tabelle con i dati riferiti ai contenuti per scatole ed ai pesi degli imballi sono aggiornate al momento della stampa del catalogo, pertanto i dati elencati possono subire variazioni.

Marazzi Group ha la facoltà esclusiva di modificare e sostituire, anche solo parzialmente i componenti dei sistemi illustrati in questo folder, senza l'obbligo di darne preavviso.



MARAZZI